

Antenna review

2.4GHz inverted F antenna on a 0.8mm FR4 PCB

Author: Jonathan Alexander Kreuzeder, intern

31.07.2023

General

Original source of the antenna:

https://github.com/sad-electronics/wch-kicad-lbr/blob/main/footprints/wch-antenna.pretty/ANT-F-1-2.4G-0.8MM-FR4-WCH.kicad_mod

Modified by Xdevelop: No

Simulation software: Dassault Systems CST Studio Suite® 2023

Number of tetrahedrons: 56,072

Matched: No

If you have any questions, contact

Bernhard Wörndl-Aichriedler


bwa@xdevelop.at

PCB data


Stackup:

Layer	Thickness	Material	Dielectric constant ϵ_r
Top	35 μ m	Copper	Not relevant
Core	0.73mm	FR4 (epoxy resin + fiberglass)	4.3
Bottom	35 μ m	Copper	Not relevant


PCB dimensions & layout




3D model of the PCB from the front




3D model of the PCB from the back




S-parameter




Radiation efficiency




Total efficiency




VSWR




Impedance Z




Maximum E-field (front)



Maximum E-field (back)




Farfield viewed from the upper edge (-y) of the PCB



— farfield (f=2450)

Frequency = 2450 MHz
Main lobe magnitude = 1.29 dBi
Main lobe direction = 7.0 deg.


Farfield viewed from the right edge (-x) of the PCB



— farfield (f=2450)

Frequency = 2450 MHz
Main lobe magnitude = 1.31 dBi
Main lobe direction = 6.0 deg.
Angular width (3 dB) = 289.9 deg.


Farfield viewed from the top (-z) of the PCB



— farfield (f=2450)

Frequency = 2450 MHz
Main lobe magnitude = 1.06 dBi
Main lobe direction = 33.0 deg.
Angular width (3 dB) = 126.4 deg.
Side lobe level = -0.5 dB

3D-Farfield (perspective)



3D-Farfield (perspective)

